ONLINE CERTIFICATIONS DIRECTORY

ZPMV2.E130014
Wiring, Printed - Component

If you notice a change to your ZPMV2 Listing Card, click here to learn more.

For enhanced search functionality, please visit UL's iQ™ Family of Databases.

Click on a product designation for complete information.

Page Bottom

Wiring, Printed - Component

See General Information for Wiring, Printed - Component

SCHALTUNGSDRUCK STORZ GMBH & CO KG E130014

CARL-BENZ-STR 1

79341 KENZINGEN, GERMANY

	Cond Width				Max			Max			
		Min	Cond	SS /	Area	Solder		Oper		Meets	C
	Min	Edge	Thk	DS /	Diam	Limits		Temp	Flame	UL796	T
Type	mm (in)	mm (in)	mic (mil)	DSO	mm (in)	C	sec	C	Class	DSR	I
Multilayer printed wiring boards.											
M1	0.1 (0.004)	0.3 (0.012)	16.5 (0.65) Int:102	DS	50.8 (2.0)	288	20	130	V-0	All	1
M2	0.1 (0.004)	0.3 (0.012)	16.5 (0.65) Int:102	DS	50.8 (2.0)	288	20	130	V-0	All	2
M3 (Note 1)	0.1 (0.004)	0.3 (0.012)	16.5 (0.65) Int:102	DS	50.8 (2.0)	288	20	130	V-0	All	3
Single layer printed wiring boards.											
S2 (Note 1)	0.1 (0.004)	0.3 (0.012)	16.5 (0.65)	DS	50.8 (2.0)	288	20	130	V-0	All	3
S3	0.1 (0.004)	0.3 (0.012)	16.5 (0.65)	DS	50.8 (2.0)	288	20	130	V-0	All	1

(Note 1) - The maximum external Cu thickness is material dependent, with some materials permitted to use up to 250microns.

Marking: Company name or trademark  or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2018-01-06

Questions? Print this page Terms of Use Page Top