



Overview of services (In-House manufacture capabilities)

Production documents	data via email, digitalization of film templates possible	
Data format	DPF, Gerber, extended Gerber, HPGL, Eagle.BRD files	
Product range	single-layer, double-layer, multilayer, HDI	
Max. number of layer	12 layers, more on request	
Board thickness	1.0 mm – 3.2 mm	
Max. usable panel size	490 x 580 [mm x mm] or 500 x 570 [mm x mm]	
Laminate type	FR-4 acc. to IPC 4101/21, TG 150, halogen-free, FR-4 high Tg-material on request	
Multilayer core	from 0.1 mm; copper lamination 18, 35, 70 and 105 µm, others on request	
Copper plating	through hole plating 25 µm, final copper thickness 35, 70, 105, 210 µm, other copper thicknesses on request	
Conductor structure	100 µm, less on request	
Drilling hole size	min. hole diameter plated: 0.20 mm microvias ≥ 80 µm	
Aspect ratio	max. 1:10	
Surface finish	ENIG, HAL lead free, immersion tin	
Solder mask	semi-matt, green, blue, red, white*, black*	
Additional print	legend print, peelable mask, via plugging / filling type 3a / 7	
Contour machining	milling, scoring (also jump scoring), chamfers 45° and 20° (PCI) also set back, depth milling and countersinking on request	
Testing	electrical test, AOI for inner layers, AVI for outer layers, 100% final test, impedance calculation and impedance test	
Approvals	UL File <u>E130014</u> , DIN EN ISO 9001, DIN EN ISO 14001, DIN EN ISO 50001	
Production standard	IPC 6012 class 2, class 3 by agreement	
Lead time	15 WD (working days)	
Express service	double-layer (2L):	≥ 3 WD
	multilayer (ML):	≥ 5 WD
	multilayer (ML) Ni/Au:	≥ 7 WD

* special design rules apply

Do you have further requirements or questions? Please contact us, we will be glad to help you.

Schaltungsdruck Storz GmbH + Co. KG
Carl-Benz-Str. 1
79341 Kenzingen

phone: +49 7644 9163-0
telefax: +49 7644 8146
email: vertrieb@storz-pcb.de